## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (original) A method of allocating switch requests within a packet switch, the method comprising the steps of
- (a) generating switch request data for each input port indicative of the output ports to which data packets are to be transmitted;
- (b) processing the switch request data for each input port to generate request data for each input port-output port pairing; and
- (d) generating an allocation plan by sorting the request data *R* relating to each of the input/output pairs in terms of their queue length, and
- (e) for each input/output pair, considered in the sorted order, allocating as many of the requests in the queue as can be accommodated in the remaining time slots.
- 2. (original) A method of packet switching wherein the packets are switched on the basis of the allocated routing, and to a packet switch in which the input port-output port routing is allocated in accordance with claim 1, and packets are switched from an input port to a specified output port in accordance with the allocated routing.
- 3. (currently amended) A method according to claim 1 or 2, in which unallocated switch requests are reserved for use in the next phase of switch request allocation, or abandoned if they have exceeded a predetermined expiry time.
- 4. (currently amended) A method according to claim 1,<del>2 or 3,</del> comprising a preliminary stage in which the number of requests for each input or output port is reduced by a factor such that the number of requests relating to that port is no greater than the number of available time slots.

## BIANCO et al U.S. National Phase of PCT/GB2003/003412

- 5. (currently amended) A method according to claim 1, <del>2 or 3,</del> comprising a preliminary stage in which the number of requests in respect of each input/output pair are reduced by a single common factor such that the number of requests relating to all ports is no greater than the number of available time slots.
- 6. (currently amended) A method of packet switching wherein the input portoutput port routing is allocated according to the method of any preceding claim claim 1 and the packets are switched on the basis of the allocated routing.
- 7. (currently amended) A packet switch in which the input port-output port routing is allocated in accordance with the method of any of claims 1 to 6 claim 1.
- 8. (original) A packet switch according to claim 7, wherein packets are switched from an input port to a specified output port in accordance with the allocated routing.